

FWA - 400



Engine

Cummins QSL
9.0 Litre Displacement (506cu. In.)
Turbocharged & air to air aftercooled
Dry Dual Element Air Cleaner
Peak 400 HP @ 2100 rpm
Torque Rise 33% @ 1500 rpm

Powershift Transmission

16 Forward Speeds / 9 Reverse Speeds
Full Power Shift, one lever control
Forward / Reverse Power Shuttle
Sequential shift, auto shift, pulse shift
Speed matching & pre-select gears
Neutral lock starting switch
Electro-Hydraulic Diff Lock
Wet Multi Disc Clutch
Independent Oil Immersed Disc Brakes
Radar
Rear Bar Axle size 120mm

Drawbar & Hydraulics

Load Sensing Closed Centre Hydraulics
208 l/min Total Flow
102 l/min Max Flow through a valve
4 Electro-Hydraulic Remotes
Ball Type (Cat.3) Lower Link Ends
Quick Hitch (Cat.4) Frame
Lift Capacity 8,410 kg
Linkage Control Buttons on Both Rear Guards
Rear Mud Guard Extensions
1000 PTO
Swinging Draw Bar
GPS ready including RAVEN valve

Lighting

2 Hood Mounted Lights
2 Front and Two Rear Halogen Worklights
4 Roof Mounted Worklights
2 LED Extremity Lights on Hood

Front Axle

Hydrostatic Power Steering
Front suspension axle
Electronic 4WD Engagement with Auto
Front Weights 33 x 30kg (990kg)
Dynamic Front Fenders

Operator Environment

Deluxe Cab Package
Air Conditioning with Heating and Ventilation
Digital Dash
High Definition Programmable Information Screen
Side Mounted Exhaust
Front and Rear Window Wiper and Washer
Telescopic Rear View Mirrors
Adjustable and Tilting Steering Column
Air Suspension Comfort Seat
Instructor Seat

Weights and Dimensions

Length with Weights	6350 mm
Overall Height	3396 mm
Wheelbase	3275 mm
Shipping Weight	10,984 kg
Max Operating Weight	16,057 kg
Fuel Capacity	643 Litres

Standard Tyres and Wheel Weights

Front 480/70R34 Rear 480/80R50 Duals
or
Front 600/65R30 Rear 710/70R42 Duals

Rear wheel weights (2*200kg = 400kg)

Warranty

2 years or Max 2000 hours from Installation

Effective July 2018